

RICHARDS BAY CLEAN AIR ASSOCIATION

DUSTFALL MONITORING

APRIL 2008

Sampling period: 20 March to 17 April 2008

Monthly Progress Report

Contact Person: Q. Hurt
Designation: Managing Director

Project Leader: M. Antoni
Consultant
H.J. Annegarn

Project Officers: L. Khumalo
Z. Mpina
J. Smith
H. Nuwarinda

ANNEGARN ENVIRONMENTAL RESEARCH
P.O. BOX 30981
BRAAMFONTEIN
2017

13 May 2008

AER 28.255M_RBCAA

1. METHODOLOGY

This project commenced operation in June 2006. Windblown settle-able dust (fall-out) is monitored using the American Society for Testing and Materials standard method for collection and analysis of dustfall (ASTM D1739). This method employs a simple device consisting of a cylindrical 5 L container half-filled with de-ionised water exposed for one calendar month (30 ± 3 days). The water is treated with an inorganic biocide to prevent algal growth in the buckets. The most common reagent used for this is a 5% copper sulphate solution (approximately 1 ml per 3 litres of water bucket).



Figure 1: Single bucket monitoring unit, showing sampling bucket with bird ring and security clamp

The bucket stand comprises a ring that is raised above the rim of the bucket to prevent contamination from perching birds (Fig 1). The bucket holder is connected to a 2.1 m galvanized steel pole, which is either directly attached to a fence post or can be attached to a galvanized steel base plate, which is buried to a depth of 500 mm. This allows for a variety of placement options for the fallout samplers. Exposed buckets, when returned to the AER laboratories, are rinsed with deionised water to remove residue from the sides of the bucket, and the bucket contents filtered through a coarse (>1 mm) filter to remove insects and other coarse organic detritus. The sample is then filtered through a pre-weighed paper filter to remove the insoluble fraction, or dust fallout. This residue and filter are dried, and gravimetrically analysed to determine the insoluble fraction (dust fallout).

1.1 Operational Aspects

The sampling period was from 20 March to 17 April 2008 and samples were exposed for 28 days. The period complies with the standard exposure period of 30 ± 3 days. No operational problems were encountered in April monitoring month and a valid sample return of 100% was achieved. It was reported that there is manufacturing of Ferro metals opposite Site 2 (SAPS Garage – Alton North), action

blasting near Site 3 (Alton South West) and construction near Site 12 (Meerensee School).

2. STANDARDS FOR DUST DEPOSITION

The Standards South Africa has published a new set of dustfall standards (SANS 1929:2005). These standards have been used to evaluate the level of dust deposition and are stated in Table 1 and Table 2 below.

2.1 Evaluation criteria for dust deposition

Dust deposition rates shall be expressed in units of $\text{mg}/\text{m}^2/\text{day}$ over a 30-days averaging period. Dust deposition is evaluated against a four-band scale as presented in Table 1. Target, action and alert thresholds indicated in and permissible frequency of exceedances are given in Table 2. Margins of tolerance are outline in Section 2.2 and allowances for exceptions in Section 2.3

Table 1: Four-band scale evaluation criteria for dust deposition (SANS 1929:2005).

Band Number	Band Description Label	Dustfall rate (D) ($\text{mg}/\text{m}^2/\text{day}$, 30-day average)	Comment
1	Residential	$D < 600$	Permissible for residential and light commercial
2	Industrial	$600 < D < 1\ 200$	Permissible for heavy commercial and industrial
3	Action	$1\ 200 < D < 2\ 400$	Requires investigation and remediation if two sequential months lie in this band, or more than three occur in a year.
4	Alert	$2\ 400 < D$	Immediate action and remediation required following the first incidence of dustfall rate being exceeded. Incident report to be submitted to relevant authority.

Table 2. New dustfall standards, target, action and alert thresholds for dust deposition (SANS 1929:2005).

Level	Dustfall Rate ($\text{mg}/\text{m}^2/\text{day}$)	Permitted Frequency of Exceedances
Target	300	
Action residential	600	Three within any year, no two sequential months.
Action industrial	1 200	Three within any year not sequential months.
Alert threshold	2 400	None. First exceedance requires remediation and compulsory report to authorities.

2.2 Margin of tolerance

An enterprise may submit a request to the authorities to operate within band 3 (action band), as specified in Table 1, for a limited period, provided that this is essential in terms of the practical operation of the enterprise (for example the final removal of a tailings deposit) and provided that an appropriate control technology is applied for the duration. No margin of tolerance will be granted for operations that result in dustfall rates which fall within band 4 (alert band) as specified in Table 1.

2.3 Exceptions

Dustfalls that exceed the specified rates but that can be shown to be the result of some extreme weather or geological event shall be discounted for the purpose of enforcement and control. Such event might typically result in excessive dustfall rates across an entire metropolitan region, and not be localized to a particular operation. Natural seasonal variations, for example, the naturally windy months each year, will not be considered extreme events for this definition.

2.4 Application of standards

Dust deposition rates recorded at RBCAA are appraised according to the standards published by the Standards South Africa (SANS 1929:2005). Dustfall rates within the RESIDENTIAL and INDUSTRIAL ranges do not result in complaints from the public. ACTION and ALERT ranges, generally result in complaints from the public, and therefore considered to be action levels, at which sources of excessive dust must be investigated (if not known) and suitable mitigation measures instituted.

3. RESULTS

During the April 2008 reporting month, all the monitoring sites recorded dustfall rates within the RESIDENTIAL threshold. Site 3 (Alton South West) recorded the highest dustfall rate of 243 mg/m²/day. Site 12 (Meerensee School) recorded the lowest dustfall rate of 31 mg/m²/day, all within that range. Trends of the dust fallout results per site are presented in Appendix A of this report.

4. Recommendations and Actions


- RESIDENTIAL threshold levels were recorded at all the monitoring sites. The results were considered satisfactory as they will not result in community complaints or nuisance.

Regards

T. Mfenqa

For AER (Pty) Ltd



Report compiled by H. Nuwarinda



Figure 1: Graph showing results from all sites: April 2008



RICHARDS BAY CLEAN AIR ASSOCIATION DUSTFALL MONITORING			Month: April 2008 Sampling period: 20 March - 17 April 2008		
SITE DESCRIPTION	SITE No.	FILTER CODE	NETT MASS (mg)	No. DAYS	DUST FALLOUT (mg/m ² /day)
Brackenham	1	RBCAA 08/97	51	28	80
SAPS Garage	2	RBCAA 08/98	54	28	84
Alton South West	3	RBCAA 08/99	155	28	243
Harbour West	4	RBCAA 08/100	37	28	58
CBD(Municipal office)	5	RBCAA 08/101	138	28	216
Scorpio	6	RBCAA 08/102	72	28	113
Alton fire station	7	RBCAA 08/103	80	28	125
Nseleni Municipal office	8	RBCAA 08/104	154	28	241
Empangeni police station	9	RBCAA 08/105	31	28	48
Felixton Village	10	RBCAA 08/106	25	28	39
Arboretum	11	RBCAA 08/107	69	28	107
Meerensee School	12	RBCAA 08/108	20	28	31



Comments:



APPENDIX A RBCAA DUST FALLOUT MONTHLY TIMEPLOTS 2006 – 2008















APPENDIX B

